

GPS/GLONASS Vehicle Tracker



T1

Tire pressure monitoring

Fully integrated for tire pressure monitoring system to enhance safety of your fleet.

CAN bus interface (Optional)

Compatible with Inventure CAN bus interface which can read CAN data of various vehicle models.

Multifunctional

Support camera, RFID, LCD/LED display, fuel/temperature sensor, and iButton driver ID.

Multiple alerts & reports

Support speeding/towing/geo-fence alerts, cornering/mileage reports etc.



APPLICATION



Bus



School bus



Sanitation vehicle



Ambulance

SPECIFICATIONS

ITEM	SPECIFICATIONS
Dimension	105 mm x 65 mm x 26 mm
Weight	190g
Power supply	DC 11–36 V/1.5 A
Backup battery	400 mAh/3.7 V
Power consumption	Current in standby mode: 65 mA
Operating temperature	-20°C to 55°C
Operating humidity	5% to 95%
Working hour	61 hours in power-saving mode, 5.7 hours in normal mode
LED indicator	Green indicator showing the GSM signal Blue indicator showing the GPS signal
Button/Switch	1 SOS button (for sending SMSs or dialing) 1 power button
Memory	8 MB buffer
Sensor	3-axis accelerometer (used to wake the device up by vibration and detect towing alerts)
Frequency band	GSM 850/900/1800/1900 MHz
GPS sensitivity	-161 dB
Positioning accuracy	2.5m
I/O port	3 digital inputs (2 negative inputs and 1 positive input) 2 analog detection inputs 3 outputs 1 RS232 port 1 USB port 1-Wire® iButton 1-Wire® temperature sensor



ACCESSORIES

T1 with a built-in battery
I/O cable + SOS button
GPS antenna
GSM antenna
USB cable
CD download card



OPTIONAL ACCESSORIES

Camera
RFID reader
A53 fuel level sensor
Handset
LED display
iButton
Tire pressure sensor
A52 digital temperature sensor + A61 sensor box



RoHS



+86(755)83462818



www.meitrack.com



info@meitrack.com



6/F, West Tower, Cafu Plaza (Sheraton Hotel), No. 5, Guihua Rd.,
Futian Free Trade Zone, Shenzhen, China. 518038